



SPECIFICATIONS

VREDESTEIN AW

Built for smaller implement applications, the Vredestein AW is the ideal solution for tilling equipment, small balers, manure spreaders and small transport equipment.

FEATURES:

Strong, flexible nylon carcass construction ensures high load capacity.

Large soil contact surface area reduces damage to soil structure, and ensures minimal rutting.

Advanced tread design ensures excellent stability and prolonged tread life.



10.0/80 - 12 IMP 116 A8 TL AW

EAN						8714692262883		Section Width				265 mm	
Nominal Tyre Pressure						3,1 bar		Overall Diameter				725 mm	
Tyre Construction						Bias		Static Loaded Radius				330 mm	
Recommended Rim Width						7.00		Rolling Circumference				2185 mm	
Permitted Rim Width								Tread Depth				10 mm	
EAN Tube						8714692238994							
Tyre Pressure (Bar)													
		1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00		

LLV		Load Capacity per tyre (kg)									HLV
Speed (km/h)	10	910	1040	1160	1260	1370	1470	1560	1650	1730	2050
	25	775	885	980	1070	1160	1250	1320	1400	1470	1740
	30	730	830	925	1010	1090	1170	1250	1320	1390	1640
	40			825	905	975	1050	1110	1180	1240	1470
	50				815	880	940	1000	1060	1110	1320

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.