



SPECIFICATIONS

VREDESTEIN AW

Built for smaller implement applications, the Vredestein AW is the ideal solution for tilling equipment, small balers, manure spreaders and small transport equipment.

FEATURES:

Strong, flexible nylon carcass construction ensures high load capacity.

Large soil contact surface area reduces damage to soil structure, and ensures minimal rutting.

Advanced tread design ensures excellent stability and prolonged tread life.



15.0/55 - 17 IMP 134 A8 TL AW

EAN						8714692263293		Section Width				385 mm	
Nominal Tyre Pressure						2,6 bar		Overall Diameter				865 mm	
Tyre Construction						Bias		Static Loaded Radius				390 mm	
Recommended Rim Width						13.00		Rolling Circumference				2580 mm	
Permitted Rim Width								Tread Depth				12 mm	
EAN Tube						8714692239069							
Tyre Pressure (Bar)													
		1.00	1.20	1.40	1.60	1.80	2.00	2.20	2.40	2.60	3.60		

LLV		Load Capacity per tyre (kg)									HLV
Speed (km/h)	10	1530	1720	1910	2105	2250	2435	2625	2810	2970	3775
	25	1300	1465	1625	1790	1910	2070	2230	2390	2525	3210
	30	1225	1375	1530	1680	1800	1950	2100	2250	2375	3020
	40			1365	1500	1605	1740	1875	2005	2120	2695
	50					1445	1565	1685	1805	1910	2425

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.