



## SPECIFICATIONS

# VREDESTEIN AW

Built for smaller implement applications, the Vredestein AW is the ideal solution for tilling equipment, small balers, manure spreaders and small transport equipment.

### FEATURES:

Strong, flexible nylon carcass construction ensures high load capacity.

Large soil contact surface area reduces damage to soil structure, and ensures minimal rutting.

Advanced tread design ensures excellent stability and prolonged tread life.



### 15.0/70 - 18 IMP 151 A8 TL AW

EAN						8714692263309		Section Width			395 mm		
Nominal Tyre Pressure						4,3 bar		Overall Diameter			1000 mm		
Tyre Construction						Bias		Static Loaded Radius			460 mm		
Recommended Rim Width						13		Rolling Circumference			3030 mm		
Permitted Rim Width								Tread Depth			13 mm		
EAN Tube						8714692239106							
Tyre Pressure (Bar)													
		1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.25	5.75			

LLV		Load Capacity per tyre (kg)								HLV
Speed (km/h)	<b>10</b>	2090	2650	3140	3560	3980	4340	4700	4860	5820
	<b>25</b>	1780	2250	2660	3040	3380	3700	4000	4140	4940
	<b>30</b>	1670	2120	2510	2860	3180	3480	3760	3900	4640
	<b>40</b>		1890	2240	2550	2840	3100	3360	3480	4160
	<b>50</b>			2010	2290	2550	2790	3020	3140	3740

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT [WWW.VREDESTEINTYRES.COM.AU](http://WWW.VREDESTEINTYRES.COM.AU)