



SPECIFICATIONS

VREDESTEIN V64+

A special carcass construction ensures that the V64+ is extremely durable and stands up very well to penetration by thorns or stones. Its special tread and rounded shoulders ensure limited damage to turf areas and offer superb stability.

FEATURES:

Durable, extra thick tread design ensures reduced rutting and lengthens tyre life.

Outstanding tyre height/width ratio ensures maximum stability on and off the road.

Rounded shoulders prevent damage to turf and sensitive crops.



170/60 - 8 65 A8 TT V64+			
EAN	8714692256462	Section Width	170 mm
Nominal Tyre Pressure	2,4 bar	Overall Diameter	410 mm
Tyre Construction	Bias	Load Capacity at 10 km/h	405 kg
Recommended Rim Width	5.50A	Load Capacity at 30 km/h	325 kg
Permitted Rim Width	5.375I	Load Capacity at 40 km/h	290 kg
		EAN Tube	8714692238918

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.