



## SPECIFICATIONS

# TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



### 280/85 R 24 115 A8/B TL Traxion85

EAN					8714692244551		Section Width			295 mm	
Nominal Tyre Pressure					1,6 bar		Overall Diameter			1090 mm	
Tyre Construction					Radial		Static Loaded Radius			520 mm	
Recommended Rim Width					W10		Rolling Circumference			3275 mm	
Permitted Rim Width					W9		SRI			525	
Alternative Size Description					11.2 R 24		Tread Depth			37 mm	
EAN Tube					8714692239724		75% of the Tyre Volume			75 l	
Tyre Pressure (Bar)											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

### Load Capacity per tyre (kg)

Speed (km/h)	10L	1000	1135	1275	1410	1550	1660	1755	1860
	10H	775	895	1020	1140	1225	1300		
	25	800	930	1055	1185	1270	1350		
	30	775	895	1020	1140	1225	1300		
	40		840	955	1065	1145	1215		
	50		840	955	1065	1145	1215		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.