



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



280/85 R 28 118 A8/B TL Traxion85

EAN					8714692309779		Section Width			285 mm	
Nominal Tyre Pressure					1,6 bar		Overall Diameter			1195 mm	
Tyre Construction					Radial		Static Loaded Radius			555 mm	
Recommended Rim Width					W10		Rolling Circumference			3540 mm	
Permitted Rim Width					W9		SRI			575	
Alternative Size Description					11.2 R 28		Tread Depth			36 mm	
EAN Tube					8714692239762		75% of the Tyre Volume			90 l	
Tyre Pressure (Bar)											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

Load Capacity per tyre (kg)

Speed (km/h)	10L	1080	1225	1375	1520	1670	1790	1895	2005
	10H	835	965	1100	1230	1320	1410		
	25	865	1005	1140	1275	1370	1465		
	30	835	965	1100	1230	1320	1410		
	40		905	1025	1150	1235	1320		
	50		905	1025	1150	1235	1320		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.