



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



320/70 R 24 116 D TL Traxion+ (70 Series)									
EAN	8714692276712				Section Width	320 mm			
Nominal Tyre Pressure	1,6 bar				Overall Diameter	1095 mm			
Tyre Construction	Radial				Static Loaded Radius	520 mm			
Recommended Rim Width	W10				Rolling Circumference	3280 mm			
Permitted Rim Width	W9, W11				SRI	525			
					Tread Depth	36 mm			
					75% of the Tyre Volume	85 l			
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	10L	1040	1180	1325	1465	1610	1725	1820	1930
	10H	860	1000	1135	1275	1365	1440		
	25	890	1030	1170	1310	1410	1480		
	30	860	1000	1135	1275	1365	1440		
	40		955	1085	1210	1300	1370		
	50		915	1040	1160	1250	1315		
	65			990	1105	1190	1250		
	70			900	1005	1080	1140		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.