



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



320/85 R 24 TL 122 A8/B Traxion85

EAN					8714692109751	Section Width				335 mm
Nominal Tyre Pressure					1,6 bar	Overall Diameter				1145 mm
Tyre Construction					Radial	Static Loaded Radius				540 mm
Recommended Rim Width					W11	Rolling Circumference				3430 mm
Permitted Rim Width					W9, W/DW10	SRI				550
Alternative Size Description					12.4 R 24	Tread Depth				40 mm
EAN Tube					8714692239731	75% of the Tyre Volume				100 l
Tyre Pressure (Bar)										
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	

Load Capacity per tyre (kg)

Speed (km/h)	10L	1225	1395	1565	1730	1900	2035	2155	2280
	10H	950	1100	1250	1400	1505	1605		
	25	985	1140	1295	1450	1560	1665		
	30	950	1100	1250	1400	1505	1605		
	40		1030	1170	1310	1405	1500		
	50		1030	1170	1310	1405	1500		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.