



## SPECIFICATIONS

# TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



### 320/85 R 28 124 A8/B TL Traxion85

EAN					8714692109782		Section Width			335 mm	
Nominal Tyre Pressure					1,6 bar		Overall Diameter			1250 mm	
Tyre Construction					Radial		Static Loaded Radius			585 mm	
Recommended Rim Width					W11		Rolling Circumference			3725 mm	
Permitted Rim Width					W9, W/DW10		SRI			600	
Alternative Size Description					12.4 R 28		Tread Depth			40 mm	
EAN Tube					8714692239779		75% of the Tyre Volume			115 l	
Tyre Pressure (Bar)											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

### Load Capacity per tyre (kg)

Speed (km/h)	<b>10L</b>	1320	1500	1680	1860	2045	2190	2315	2455
	<b>10H</b>	1020	1185	1345	1505	1615	1710		
	<b>25</b>	1055	1225	1395	1560	1675	1775		
	<b>30</b>	1020	1185	1345	1505	1615	1710		
	<b>40</b>		1105	1255	1405	1510	1600		
	<b>50</b>		1105	1255	1405	1510	1600		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.