



SPECIFICATIONS

TRACTION FLOTATION+

When you want a bumper crop, the last thing you want is compacted soil to spoil it. The excellent flotation properties of Vredestein Flotation+ ensures limited soil compaction to allow excellent seed germination.

FEATURES:

Wide tread design with a large ground contact surface area ensures excellent flotation properties and minimal soil compaction.

Unique tread design ensures excellent self-cleaning properties.

Excellent height/width ratio ensures optimal stability.



340/55 - 16 IMP 133 A8 TL FLOTATION+

EAN					8714692220432		Section Width			345 mm
Nominal Tyre Pressure					3,2 bar		Overall Diameter			780 mm
Tyre Construction					Bias		Static Loaded Radius			365 mm
Recommended Rim Width					11		Rolling Circumference			2360 mm
							Tread Depth			14 mm
Tyre Pressure (Bar)										
		1,00	1,40	1,80	2,20	2,60	3,00	3,20	4,00	

LLV		Load Capacity per tyre (kg)							HLV
Speed (km/h)	10	1300	1590	1870	2160	2450	2740	2880	3460
	25	1100	1350	1590	1840	2080	2330	2450	2940
	30	1040	1270	1500	1730	1960	2190	2310	2770
	40		1130	1340	1540	1750	1960	2060	2470
	50			1210	1390	1580	1760	1850	2220

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.