



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



340/85 R 24 125 A8/B TL Traxion85

EAN					8714692109768		Section Width			360 mm	
Nominal Tyre Pressure					1,6 bar		Overall Diameter			1190 mm	
Tyre Construction					Radial		Static Loaded Radius			550 mm	
Recommended Rim Width					W12		Rolling Circumference			3535 mm	
Permitted Rim Width					W11, W12L		SRI			575	
Alternative Size Description					13.6 R 24		Tread Depth			41 mm	
EAN Tube					8714692239748		75% of the Tyre Volume			125 l	
Tyre Pressure (Bar)											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

Load Capacity per tyre (kg)

Speed (km/h)	10L	1350	1530	1715	1900	2085	2235	2365	2505
	10H	1040	1210	1375	1535	1650	1765		
	25	1080	1255	1425	1595	1710	1830		
	30	1040	1210	1375	1535	1650	1765		
	40		1130	1285	1435	1540	1650		
	50		1130	1285	1435	1540	1650		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.