



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



340/85 R 38 133 A8/B TL Traxion85

EAN					8714692109850		Section Width			360 mm	
Nominal Tyre Pressure					1,6 bar		Overall Diameter			1550 mm	
Tyre Construction					Radial		Static Loaded Radius			730 mm	
Recommended Rim Width					W12		Rolling Circumference			4680 mm	
Permitted Rim Width					W11,DW12		SRI			750	
Alternative Size Description					13.6 R 38		Tread Depth			41 mm	
EAN Tube					8714692331442		75% of the Tyre Volume			170 l	
Tyre Pressure (Bar)											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

Load Capacity per tyre (kg)

Speed (km/h)	10L	1685	1910	2145	2375	2605	2790	2955	3130
	10H	1300	1510	1715	1920	2060	2205		
	25	1350	1565	1780	1990	2140	2285		
	30	1300	1510	1715	1920	2060	2205		
	40		1410	1600	1795	1925	2060		
	50		1410	1600	1795	1925	2060		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.