



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



360/70 R 24 122 D TL Traxion+ (70 Series)									
EAN	8714692276743				Section Width	360 mm			
Nominal Tyre Pressure	1,6 bar				Overall Diameter	1150 mm			
Tyre Construction	Radial				Static Loaded Radius	545 mm			
Recommended Rim Width	W11				Rolling Circumference	3445 mm			
Permitted Rim Width	W10, W12				SRI	550			
					Tread Depth	37 mm			
					75% of the Tyre Volume	115 l			
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	10L	1245	1410	1585	1750	1925	2060	2180	2310
	10H	1030	1195	1360	1520	1635	1725		
	25	1060	1235	1400	1570	1685	1780		
	30	1030	1195	1360	1520	1635	1725		
	40		1140	1295	1450	1555	1645		
	50		1095	1240	1390	1495	1575		
	65			1185	1325	1420	1500		
	70			1075	1205	1295	1365		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.