



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



380/70 R 28 127 D TL Traxion+ (70 Series)									
EAN	8714692276811				Section Width	390 mm			
Nominal Tyre Pressure	1,6 bar				Overall Diameter	1295 mm			
Tyre Construction	Radial				Static Loaded Radius	620 mm			
Recommended Rim Width	W12				Rolling Circumference	3895 mm			
Permitted Rim Width	W11, W12L, W13				SRI	625			
					Tread Depth	38 mm			
EAN Tube	8714692239786				75% of the Tyre Volume	155 l			
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	10L	1450	1650	1850	2050	2250	2410	2550	2700
	10H	1205	1400	1590	1780	1910	2010		
	25	1240	1440	1640	1835	1970	2075		
	30	1205	1400	1590	1780	1910	2010		
	40		1330	1515	1695	1820	1915		
	50		1275	1450	1625	1745	1840		
	65			1385	1545	1660	1750		
	70			1260	1410	1510	1595		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.