



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



380/85 R 24 131 A8/B TL Traxion85

EAN	8714692109775	Section Width	400 mm
Nominal Tyre Pressure	1,6 bar	Overall Diameter	1240 mm
Tyre Construction	Radial	Static Loaded Radius	580 mm
Recommended Rim Width	W13	Rolling Circumference	3710 mm
Permitted Rim Width	W11, W12(L), DW13(L)	SRI	600
Alternative Size Description	14.9 R 24	Tread Depth	43 mm
EAN Tube	8714692239755	75% of the Tyre Volume	155 l

Tyre Pressure (Bar)

	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
--	------	------	------	------	------	------	------	------

Load Capacity per tyre (kg)

Speed (km/h)	10L	1600	1820	2040	2260	2480	2660	2810	2980
	10H	1235	1435	1630	1825	1960	2085		
	25	1285	1490	1695	1895	2035	2165		
	30	1235	1435	1630	1825	1960	2085		
	40		1340	1525	1705	1835	1950		
	50		1340	1525	1705	1835	1950		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.