



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



380/85 R 28 133 A8/B TL Traxion85

EAN					8714692109805		Section Width			400 mm	
Nominal Tyre Pressure					1,6 bar		Overall Diameter			1345 mm	
Tyre Construction					Radial		Static Loaded Radius			630 mm	
Recommended Rim Width					W13		Rolling Circumference			3985 mm	
Permitted Rim Width					W11, W12(L)		SRI			650	
Alternative Size Description					14.9 R 28		Tread Depth			43 mm	
EAN Tube					8714692239748		75% of the Tyre Volume			175 l	
Tyre Pressure (Bar)											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

Load Capacity per tyre (kg)

Speed (km/h)	10L	1715	1950	2185	2420	2660	2850	3010	3190
	10H	1325	1540	1750	1955	2100	2205		
	25	1375	1595	1815	2030	2180	2285		
	30	1325	1540	1750	1955	2100	2205		
	40		1440	1635	1830	1965	2060		
	50		1440	1635	1830	1965	2060		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT WWW.VREDESTEINTYRES.COM.AU