



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



380/85 R 30 135 A8/B TL Traxion85 II

EAN					8714692336591	Section Width				390 mm
Nominal Tyre Pressure					1,6 bar	Overall Diameter				1410 mm
Tyre Construction					Radial	Static Loaded Radius				645 mm
Recommended Rim Width					W12	Rolling Circumference				4150 mm
Permitted Rim Width					W11, W13	SRI				675
Alternative Size Description					14.9 R 30	Tread Depth				43 mm
						75% of the Tyre Volume				230 l
Tyre Pressure (Bar)										
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	

Load Capacity per tyre (kg)

Speed (km/h)	10L	1770	2010	2260	2500	2745	2940	3110	3295
	10H	1370	1590	1805	2020	2170	2335		
	25	1420	1650	1875	2095	2250	2420		
	30	1370	1590	1805	2020	2170	2335		
	40		1485	1685	1890	2030	2180		
	50		1485	1685	1890	2030	2180		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.