



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



380/85 R 34 137 A8/B TL Traxion85 II

EAN					8714692336607	Section Width				390 mm
Nominal Tyre Pressure					1,6 bar	Overall Diameter				1505 mm
Tyre Construction					Radial	Static Loaded Radius				80 mm
Recommended Rim Width					W12	Rolling Circumference				4470 mm
Permitted Rim Width					W11, W13	SRI				725
Alternative Size Description					14.9 R 34	Tread Depth				43 mm
						75% of the Tyre Volume				250 l
Tyre Pressure (Bar)										
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	

Load Capacity per tyre (kg)

Speed (km/h)	10L	1880	2135	2395	2655	2915	3120	3300	3500
	10H	1455	1685	1915	2145	2305	2460		
	25	1505	1750	1990	2225	2390	2555		
	30	1455	1685	1915	2145	2305	2460		
	40		1575	1790	2005	2155	2300		
	50		1575	1790	2005	2155	2300		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.