



SPECIFICATIONS

TRAXION VERSA

The Vredestein Traxion Versa is a state-of-the-art agro-industrial tyre, ideal for telehandlers, backhoes, and compact wheel loaders operating on feedlots and for general around-the-farm maintenance. It is specifically designed for use on soft surfaces where optimal traction and flotation are required.

FEATURES:

Incorporating the unique Traxion design concept, the Versa ensures exceptional comfort and traction in the field.

A large cleat surface in the comfort zone provides extensive ground contact for optimal flotation.

The extended curved cleats enhance traction.

A reinforced sidewall and stabiliser ring provide robust damage protection.



400/70 R 20 IND 149 A8/B TL TRAXION VERSA

| | | | | | | | | | |
|--|--|------------------|--|------|---------|------|------|------|------|
| EAN | | 8714692309922 | Section Width | | 405 mm | | | | |
| Nominal Tyre Pressure | | 4,0 bar | Overall Diameter | | 1075 mm | | | | |
| Tyre Construction | | Radial | Static Loaded Radius | | 475 mm | | | | |
| Recommended Rim Width | | 13 | Rolling Circumference | | 3250 mm | | | | |
| Permitted Rim Width | | 12SDC, 13SDC, 14 | SRI | | 525 | | | | |
| Alternative Size Description(s) | | 405/70 R 20 | Tread Depth (including tie bac) | | 36 mm | | | | |
| | | 16.0/70 R 20 | Tread Bar Height | | 3 mm | | | | |
| | | | 75% of the Tyre Volume | | 115 l | | | | |
| Tyre Pressure (Bar) | | | | | | | | | |
| | | 1,60 | 2,00 | 2,40 | 2,80 | 3,20 | 3,60 | 4,00 | 4,40 |

| Load Capacity per tyre (kg) | | | | | | | | | |
|------------------------------------|------------|------|------|------|------|------|------|------|------|
| Speed (km/h) | 0 | 2915 | 3590 | 4260 | 4860 | 5530 | 6205 | 6840 | 7475 |
| | 10C | 1900 | 2340 | 2780 | 3170 | 3610 | 4045 | 4460 | 4875 |
| | 25 | 1640 | 1955 | 2245 | 2640 | 2970 | 3150 | 3445 | |
| | 30 | 1610 | 1920 | 2205 | 2590 | 2910 | 3095 | 3380 | |
| | 40 | 1550 | 1845 | 2120 | 2490 | 2800 | 2975 | 3250 | |
| | 50 | 1550 | 1845 | 2120 | 2490 | 2800 | 2975 | 3250 | |

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT WWW.VREDESTEINTYRES.COM.AU