



SPECIFICATIONS

ENDURION

The Vredestein Endurion is a premium agro-industrial tyre, ideal for telehandlers, backhoes, and compact wheel loaders. It provides maximum efficiency on hard surfaces.

FEATURES:

High rubber content in the tyre construction provides exceptionally long service life.

Broad 45-degree angled cleats ensure outstanding self-cleaning ability and traction.

An advanced tyre compound and robust carcass design ensures outstanding durability and puncture resistance for prolonged tyre life and optimal return on investment.



400/70 R 24 IND 152 A8/B TL ENDURION

EAN		8714692335402	Section Width		405 mm				
Nominal Tyre Pressure		4,0 bar	Overall Diameter		1170 mm				
Tyre Construction		Radial	Static Loaded Radius		540 mm				
Recommended Rim Width		13	Rolling Circumference		3510 mm				
Permitted Rim Width		W10, W11,	SRI		500				
		12SDC, 13SDC, 14	Tread Depth (including tie bac)		25 mm				
Alternative Size Description(s)		405/70 R 24	Tread Bar Height		3 mm				
		16.0/70 R 24	75% of the Tyre Volume		130 l				
Tyre Pressure (Bar)									
		1,60	2,00	2,40	2,80	3,20	3,60	4,00	4,40

Load Capacity per tyre (kg)									
Speed (km/h)	0	3150	3850	4550	5250	5950	6670	7350	8165
	10C	2055	2510	2965	3425	3880	4350	4795	5325
	25	1775	2095	2420	2740	3075	3385	3765	
	30	1740	2055	2375	2690	3015	3325	3690	
	40	1675	1980	2285	2585	2900	3195	3550	
	50	1675	1980	2285	2585	2900	3195	3550	

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.