



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



420/70 R 24 130 D TL Traxion+ (70 Series)									
EAN	8714692276774				Section Width	430 mm			
Nominal Tyre Pressure	1,6 bar				Overall Diameter	1245 mm			
Tyre Construction	Radial				Static Loaded Radius	595 mm			
Recommended Rim Width	W13				Rolling Circumference	3755 mm			
Permitted Rim Width	W12(L), DW13(L), W/DW14L				SRI	600			
EAN Tube	8714692239755				Tread Depth	42 mm			
	75% of the Tyre Volume				175 l				
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	10L	1575	1790	2005	2220	2440	2615	2765	2930
	10H	1305	1515	1725	1930	2075	2185		
	25	1345	1565	1775	1990	2135	2250		
	30	1305	1515	1725	1930	2075	2185		
	40		1445	1640	1840	1975	2080		
	50		1385	1575	1760	1895	1995		
	65			1500	1680	1800	1900		
	70			1365	1525	1640	1730		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.