



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



### 420/70 R 28 133 D TL Traxion+ (70 Series)

<b>EAN</b>					8714692276835	<b>Section Width</b>				430 mm
<b>Nominal Tyre Pressure</b>					1,6 bar	<b>Overall Diameter</b>				1350 mm
<b>Tyre Construction</b>					Radial	<b>Static Loaded Radius</b>				640 mm
<b>Recommended Rim Width</b>					W13	<b>Rolling Circumference</b>				4055 mm
<b>Permitted Rim Width</b>					W12(L), W/DW14L	<b>SRI</b>				650
						<b>Tread Depth</b>				42 mm
<b>EAN Tube</b>					8714692239793	<b>75% of the Tyre Volume</b>				195 l
<b>Tyre Pressure (Bar)</b>										
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	

### Load Capacity per tyre (kg)

Speed (km/h)	10L	1690	1920	2155	2385	2620	2805	2965	3145
	10H	1405	1630	1850	2070	2225	2370		
	25	1445	1680	1910	2135	2295	2440		
	30	1405	1630	1850	2070	2225	2370		
	40		1550	1765	1975	2120	2255		
	50		1485	1690	1890	2030	2165		
	65			1610	1800	1935	2060		
	70			1465	1640	1760	1875		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT [WWW.VREDESTEINTYRES.COM.AU](http://WWW.VREDESTEINTYRES.COM.AU)