



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



420/85 R 24 137 A8/B TL Traxion85

EAN	8714692206344	Section Width	450 mm
Nominal Tyre Pressure	1,6 bar	Overall Diameter	1320 mm
Tyre Construction	Radial	Static Loaded Radius	620 mm
Recommended Rim Width	DW15L	Rolling Circumference	3925 mm
Permitted Rim Width	W/DW13(L), W/DW14L, W15L	SRI	625
Alternative Size Description	16.9 R 24	Tread Depth	45 mm
EAN Tube	8714692283727	75% of the Tyre Volume	210 l

Tyre Pressure (Bar)

	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
--	------	------	------	------	------	------	------	------

Load Capacity per tyre (kg)

Speed (km/h)	10L	1875	2130	2390	2645	2905	3110	3290	3485
	10H	1450	1680	1910	2140	2295	2460		
	25	1500	1745	1980	2220	2380	2555		
	30	1450	1680	1910	2140	2295	2460		
	40		1570	1785	2000	2145	2300		
	50		1570	1785	2000	2145	2300		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT WWW.VREDESTEINTYRES.COM.AU