



## SPECIFICATIONS

# TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



### 420/85 R 28 139 A8/B TL Traxion85

EAN					8714692109812		Section Width			455 mm	
Nominal Tyre Pressure					1,6 bar		Overall Diameter			1415 mm	
Tyre Construction					Radial		Static Loaded Radius			660 mm	
Recommended Rim Width					DW15L		Rolling Circumference			4215 mm	
Permitted Rim Width					W13, W/DW14L,		SRI			675	
					W15L		Tread Depth			45 mm	
Alternative Size Description					16.9 R 28		75% of the Tyre Volume			235 l	
EAN Tube					8714692239809						
Tyre Pressure (Bar)											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

Load Capacity per tyre (kg)									
Speed (km/h)	10L	2005	2275	2555	2825	3105	3325	3515	3725
	10H	1550	1795	2040	2285	2455	2600		
	25	1605	1865	2120	2370	2545	2695		
	30	1550	1795	2040	2285	2455	2600		
	40		1680	1910	2135	2295	2430		
	50		1680	1910	2135	2295	2430		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.