



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



420/85 R 30 140 A8/B TL Traxion85

EAN	8714692109829	Section Width	455 mm
Nominal Tyre Pressure	1,6 bar	Overall Diameter	1470 mm
Tyre Construction	Radial	Static Loaded Radius	685 mm
Recommended Rim Width	DW15L	Rolling Circumference	4425 mm
Permitted Rim Width	W13, W/DW14L,	SRI	700
	W15L	Tread Depth	45 mm
Alternative Size Description	16.9 R 30	75% of the Tyre Volume	245 l
EAN Tube	8714692331381		

Tyre Pressure (Bar)

	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
--	------	------	------	------	------	------	------	------

Load Capacity per tyre (kg)

Speed (km/h)	10L	2070	2345	2635	2915	3200	3430	3625	3845
	10H	1595	1855	2105	2355	2530	2675		
	25	1655	1920	2185	2445	2625	2775		
	30	1595	1855	2105	2355	2530	2675		
	40		1730	1970	2205	2365	2500		
	50		1730	1970	2205	2365	2500		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.