



## SPECIFICATIONS

# TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



### 420/85 R 38 144 A8/B TL Traxion85

EAN					8714692109867		Section Width			455 mm	
Nominal Tyre Pressure					1,6 bar		Overall Diameter			1670 mm	
Tyre Construction					Radial		Static Loaded Radius			780 mm	
Recommended Rim Width					DW15L		Rolling Circumference			5035 mm	
Permitted Rim Width					W/DW14L, W15L		SRI			800	
Alternative Size Description					16.9 R 38		Tread Depth			45 mm	
EAN Tube					8714692331459		75% of the Tyre Volume			290 l	
Tyre Pressure (Bar)											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

### Load Capacity per tyre (kg)

Speed (km/h)	<b>10L</b>	2310	2625	2945	3260	3580	3835	4055	4295
	<b>10H</b>	1785	2070	2355	2635	2830	2995		
	<b>25</b>	1850	2150	2440	2735	2935	3110		
	<b>30</b>	1785	2070	2355	2635	2830	2995		
	<b>40</b>		1935	2200	2460	2645	2800		
	<b>50</b>		1935	2200	2460	2645	2800		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.