



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



440/65 R 28 131 D TL Traxion+ (65 Series)									
EAN	8714692259784				Section Width	440 mm			
Nominal Tyre Pressure	1,6 bar				Overall Diameter	1285 mm			
Tyre Construction	Radial				Static Loaded Radius	615 mm			
Recommended Rim Width	DW14L				Rolling Circumference	3890 mm			
Permitted Rim Width	W13, W14L, W/DW15L				SRI	625			
					Tread Depth	38 mm			
					75% of the Tyre Volume	180 l			
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	10L	1615	1830	2055	2275	2500	2675	2820	2995
	10H	1340	1555	1765	1950	2105	2245		
	25	1380	1600	1820	2005	2165	2310		
	30	1340	1555	1765	1950	2105	2245		
	40		1480	1680	1855	2000	2135		
	50		1420	1615	1780	1920	2050		
	65			1535	1695	1830	1950		
	70			1400	1540	1665	1775		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.