



SPECIFICATIONS

ENDURION

The Vredestein Endurion is a premium agro-industrial tyre, ideal for telehandlers, backhoes, and compact wheel loaders. It provides maximum efficiency on hard surfaces.

FEATURES:

High rubber content in the tyre construction provides exceptionally long service life.

Broad 45-degree angled cleats ensure outstanding self-cleaning ability and traction.

An advanced tyre compound and robust carcass design ensures outstanding durability and puncture resistance for prolonged tyre life and optimal return on investment.



440/80 R 28 IND 156 A8/B TL ENDURION

EAN		8714692310065	Section Width		455 mm		
Nominal Tyre Pressure		3,2 bar	Overall Diameter		1420 mm		
Tyre Construction		Radial	Static Loaded Radius		640 mm		
Recommended Rim Width		DW14L	Rolling Circumference		4290 mm		
Permitted Rim Width		DW13L, DW15L	SRI		675		
Alternative Size Description(s)		16.9 R 28	Tread Depth (including tie bac)		30 mm		
			Tread Bar Height		3 mm		
			75% of the Tyre Volume		238 l		
Tyre Pressure (Bar)							
		1,60	2,00	2,40	2,80	3,20	3,60

Load Capacity per tyre (kg)							
Speed (km/h)	0	4405	5380	6360	7340	8315	9200
	10C	2870	3510	4150	4785	5425	6000
	25	2480	2930	3380	3835	4240	
	30	2435	2875	3320	3760	4160	
	40	2340	2765	3190	3615	4000	
	50	2340	2765	3190	3615	4000	

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.