



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



460/85 R 30 145 A8/B TL Traxion85

EAN	8714692309809	Section Width	490 mm
Nominal Tyre Pressure	1,6 bar	Overall Diameter	1545 mm
Tyre Construction	Radial	Static Loaded Radius	725 mm
Recommended Rim Width	DW15L	Rolling Circumference	4605 mm
Permitted Rim Width	DW13, W/DW14L,	SRI	725
	W15L	Tread Depth	47 mm
Alternative Size Description	18.4 R 30	75% of the Tyre Volume	330 l
EAN Tube	8714692331527		

Tyre Pressure (Bar)

	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
--	------	------	------	------	------	------	------	------

Load Capacity per tyre (kg)

Speed (km/h)	10L	2380	2705	3035	3360	3690	3950	4175	4430
	10H	1840	2135	2425	2715	2915	3105		
	25	1905	2215	2515	2815	3025	3220		
	30	1840	2135	2425	2715	2915	3105		
	40		1995	2265	2535	2725	2900		
	50		1995	2265	2535	2725	2900		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.