



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



460/85 R 34 147 A8/B TL Traxion85

EAN	8714692109843	Section Width	490 mm
Nominal Tyre Pressure	1,6 bar	Overall Diameter	1640 mm
Tyre Construction	Radial	Static Loaded Radius	765 mm
Recommended Rim Width	DW16L	Rolling Circumference	4915 mm
Permitted Rim Width	W/DW14L,	SRI	775
	W/DW15L,	Tread Depth	48 mm
Alternative Size Description	W16L 18.4 R 34	75% of the Tyre Volume	340 l
EAN Tube	8714692331411		

Tyre Pressure (Bar)

	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
--	------	------	------	------	------	------	------	------

Load Capacity per tyre (kg)

Speed (km/h)	10L	2520	2860	3210	3550	3900	4180	4420	4685
	10H	1945	2255	2565	2870	3085	3290		
	25	2020	2340	2660	2980	3200	3415		
	30	1945	2255	2565	2870	3085	3290		
	40		2110	2400	2685	2885	3075		
	50		2110	2400	2685	2885	3075		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.