



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



460/85 R 38 149 A8/B TL Traxion85

EAN	8714692109874	Section Width	490 mm
Nominal Tyre Pressure	1,6 bar	Overall Diameter	1750 mm
Tyre Construction	Radial	Static Loaded Radius	815 mm
Recommended Rim Width	DW16L	Rolling Circumference	5205 mm
Permitted Rim Width	W/DW14L,	SRI	825
	W/DW15L, W16L	Tread Depth	48 mm
Alternative Size Description	18.4 R 38	75% of the Tyre Volume	365 l
EAN Tube	8714692331466		

Tyre Pressure (Bar)

	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
--	------	------	------	------	------	------	------	------

Load Capacity per tyre (kg)

Speed (km/h)	10L	2655	3010	3380	3740	4110	4400	4655	4935
	10H	2050	2380	2705	3025	3250	3480		
	25	2125	2465	2805	3140	3370	3610		
	30	2050	2380	2705	3025	3250	3480		
	40		2220	2525	2825	3035	3250		
	50		2220	2525	2825	3035	3250		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT WWW.VREDESTEINTYRES.COM.AU