



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



| 480/65 R 28 136 D TL Traxion+ (65 Series) | | | | | | | | | |
|---|--|---------------|------|------|------|------------------------|------|---------|------|
| EAN | | 8714692259791 | | | | Section Width | | 490 mm | |
| Nominal Tyre Pressure | | 1,6 bar | | | | Overall Diameter | | 1350 mm | |
| Tyre Construction | | Radial | | | | Static Loaded Radius | | 625 mm | |
| Recommended Rim Width | | DW15L | | | | Rolling Circumference | | 4020 mm | |
| Permitted Rim Width | | W/DW14, W15L | | | | SRI | | 650 | |
| | | | | | | Tread Depth | | 41 mm | |
| EAN Tube | | 8714692239793 | | | | 75% of the Tyre Volume | | 225 l | |
| Tyre Pressure (Bar) | | | | | | | | | |
| | | 0,60 | 0,80 | 1,00 | 1,20 | 1,40 | 1,60 | 1,80 | 2,00 |

| Load Capacity per tyre (kg) | | | | | | | | | |
|-----------------------------|------------|------|------|------|------|------|------|------|------|
| Speed (km/h) | 10L | 1845 | 2095 | 2350 | 2600 | 2855 | 3055 | 3225 | 3420 |
| | 10H | 1530 | 1775 | 2020 | 2225 | 2400 | 2575 | | |
| | 25 | 1575 | 1830 | 2080 | 2295 | 2475 | 2655 | | |
| | 30 | 1530 | 1775 | 2020 | 2225 | 2400 | 2575 | | |
| | 40 | | 1690 | 1920 | 2120 | 2285 | 2455 | | |
| | 50 | | 1620 | 1840 | 2030 | 2195 | 2350 | | |
| | 65 | | | 1755 | 1935 | 2090 | 2240 | | |
| | 70 | | | 1595 | 1760 | 1900 | 2040 | | |

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.