



SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

## FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



480/70 R 24 138 D TL Traxion+ (70 Series)									
<b>EAN</b>	8714692276798				<b>Section Width</b>	495 mm			
<b>Nominal Tyre Pressure</b>	1,6 bar				<b>Overall Diameter</b>	1315 mm			
<b>Tyre Construction</b>	Radial				<b>Static Loaded Radius</b>	620 mm			
<b>Recommended Rim Width</b>	DW15L W/DW14L,				<b>Rolling Circumference</b>	3950 mm			
<b>Permitted Rim Width</b>	W15L, W/DW16L				<b>SRI</b>	625			
					<b>Tread Depth</b>	48 mm			
					<b>75% of the Tyre Volume</b>	240 l			
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	<b>10L</b>	1940	2200	2470	2735	3005	3220	3405	3605
	<b>10H</b>	1610	1870	2125	2375	2555	2715		
	<b>25</b>	1660	1925	2190	2450	2630	2795		
	<b>30</b>	1610	1870	2125	2375	2555	2715		
	<b>40</b>		1780	2020	2265	2430	2585		
	<b>50</b>		1705	1940	2170	2330	2480		
	<b>65</b>			1845	2065	2220	2360		
	<b>70</b>			1680	1880	2020	2150		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.