



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



### 480/70 R 28 140 D TL Traxion+ (70 Series)

<b>EAN</b>		8714692276859	<b>Section Width</b>		495 mm				
<b>Nominal Tyre Pressure</b>		1,6 bar	<b>Overall Diameter</b>		1415 mm				
<b>Tyre Construction</b>		Radial	<b>Static Loaded Radius</b>		655 mm				
<b>Recommended Rim Width</b>		DW15L W/DW14L,	<b>Rolling Circumference</b>		4240 mm				
<b>Permitted Rim Width</b>		W15L, W/DW16L	<b>SRI</b>		675				
			<b>Tread Depth</b>		48 mm				
<b>EAN Tube</b>		8714692239809	<b>75% of the Tyre Volume</b>		255 l				
<b>Tyre Pressure (Bar)</b>									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

### Load Capacity per tyre (kg)

Speed (km/h)	10L	2075	2355	2645	2930	3215	3445	3645	3860
	10H	1725	2000	2275	2545	2735	2875		
	25	1775	2060	2345	2620	2815	2965		
	30	1725	2000	2275	2545	2735	2875		
	40		1905	2165	2425	2600	2740		
	50		1825	2075	2325	2495	2625		
	65			1975	2210	2375	2500		
	70			1800	2015	2160	2275		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT [WWW.VREDESTEINTYRES.COM.AU](http://WWW.VREDESTEINTYRES.COM.AU)