



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



480/70 R 30 141 D TL Traxion+ (70 Series)									
EAN		8714692276873				Section Width		495 mm	
Nominal Tyre Pressure		1,6 bar				Overall Diameter		1475 mm	
Tyre Construction		Radial				Static Loaded Radius		695 mm	
Recommended Rim Width		DW15L W/DW14L,				Rolling Circumference		4440 mm	
Permitted Rim Width		W15L, W/DW16L				SRI		700	
						Tread Depth		48 mm	
EAN Tube		8714692331381				75% of the Tyre Volume		270 l	
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	<b>10L</b>	2145	2435	2730	3020	3320	3555	3760	3985
	<b>10H</b>	1780	2065	2345	2625	2820	2960		
	<b>25</b>	1835	2125	2420	2705	2905	3050		
	<b>30</b>	1780	2065	2345	2625	2820	2960		
	<b>40</b>		1965	2235	2500	2685	2820		
	<b>50</b>		1885	2145	2400	2575	2705		
	<b>65</b>			2040	2285	2450	2575		
	<b>70</b>			1855	2080	2230	2345		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.