



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



### 480/70 R 34 143 D TL Traxion+ (70 Series)

<b>EAN</b>						8714692276897		<b>Section Width</b>		495 mm	
<b>Nominal Tyre Pressure</b>						1,6 bar		<b>Overall Diameter</b>		1575 mm	
<b>Tyre Construction</b>						Radial		<b>Static Loaded Radius</b>		750 mm	
<b>Recommended Rim Width</b>						DW15L W/DW14L,		<b>Rolling Circumference</b>		4765 mm	
<b>Permitted Rim Width</b>						W15L, W/DW16L		<b>SRI</b>		750	
								<b>Tread Depth</b>		48 mm	
								<b>75% of the Tyre Volume</b>		295 l	
<b>Tyre Pressure (Bar)</b>											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

### Load Capacity per tyre (kg)

Speed (km/h)	10L	2275	2580	2895	3205	3520	3770	3990	4230
	10H	1885	2190	2490	2785	2990	3135		
	25	1945	2255	2565	2870	3085	3230		
	30	1885	2190	2490	2785	2990	3135		
	40		2085	2370	2650	2850	2985		
	50		2000	2275	2545	2730	2860		
	65			2165	2420	2600	2725		
	70			1970	2205	2365	2480		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT [WWW.VREDESTEINTYRES.COM.AU](http://WWW.VREDESTEINTYRES.COM.AU)