



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



### 480/70 R 38 145 D TL Traxion+ (70 Series)

<b>EAN</b>		8714692276934	<b>Section Width</b>		495 mm				
<b>Nominal Tyre Pressure</b>		1,6 bar	<b>Overall Diameter</b>		1680 mm				
<b>Tyre Construction</b>		Radial	<b>Static Loaded Radius</b>		795 mm				
<b>Recommended Rim Width</b>		DW15L W/DW14L,	<b>Rolling Circumference</b>		5025 mm				
<b>Permitted Rim Width</b>		W15L, W/DW16L	<b>SRI</b>		800				
			<b>Tread Depth</b>		48 mm				
<b>EAN Tube</b>		8714692331459	<b>75% of the Tyre Volume</b>		320 l				
<b>Tyre Pressure (Bar)</b>									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	10L	2400	2725	3060	3385	3720	3980	4210	4465
	10H	1990	2310	2630	2940	3160	3335		
	25	2050	2380	2710	3030	3255	3435		
	30	1990	2310	2630	2940	3160	3335		
	40		2200	2500	2800	3005	3175		
	50		2110	2400	2685	2885	3045		
	65			2285	2555	2745	2900		
	70			2080	2325	2500	2640		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.