



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



480/80 R 42 156 A8/B TL Traxion85

EAN							8714692327179							Section Width				500 mm	
Nominal Tyre Pressure							2,4 bar							Overall Diameter				1850 mm	
Tyre Construction							Radial							Static Loaded Radius				855 mm	
Recommended Rim Width							DW16L							Rolling Circumference				5600 mm	
Permitted Rim Width							DD16L, W16L,							SRI				875	
							W/DW16A*							Tread Depth				49 mm	
Alternative Size Description							18.4 R 42							75% of the Tyre Volume				490 l	
Tyre Pressure (Bar)																			
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80						

Load Capacity per tyre (kg)													
Speed (km/h)	10L	2820	3200	3595	3980	4370	4680	4950	5245	5465	5655	5885	6000
	10H	2180	2530	2875	3215	3455	3690	3860	4025	4170	4280		
	25	2260	2620	2980	3335	3585	3830	4005	4175	4325	4440		
	30	2180	2530	2875	3215	3455	3690	3860	4025	4170	4280		
	40			2685	3005	3230	3450	3605	3760	3895	4000		
	50			2685	3005	3230	3450	3605	3760	3895	4000		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.