



## SPECIFICATIONS

# TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



### 480/80 R 46 158 A8/B TL Traxion85

<b>EAN</b>	8714692327193	<b>Section Width</b>	500 mm
<b>Nominal Tyre Pressure</b>	2,4 bar	<b>Overall Diameter</b>	1950 mm
<b>Tyre Construction</b>	Radial	<b>Static Loaded Radius</b>	900 mm
<b>Recommended Rim Width</b>	DW16L	<b>Rolling Circumference</b>	5885 mm
<b>Permitted Rim Width</b>	DD16L, W16L, W/DW16A*	<b>SRI</b>	925
<b>Alternative Size Description</b>	18.4 R 46	<b>Tread Depth</b>	49 mm
		<b>75% of the Tyre Volume</b>	525 l

#### Tyre Pressure (Bar)

		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
--	--	------	------	------	------	------	------	------	------	------	------	------	------

#### Load Capacity per tyre (kg)

Speed (km/h)	<b>10L</b>	2950	3350	3760	4160	4570	4895	5175	5490	5720	5915	6155	6375
	<b>10H</b>	2280	2645	3005	3365	3615	3800	4035	4210	4360	4550		
	<b>25</b>	2365	2745	3120	3490	3750	3940	4190	4370	4525	4720		
	<b>30</b>	2280	2645	3005	3365	3615	3800	4035	4210	4360	4550		
	<b>40</b>			2810	3145	3375	3550	3775	3935	4075	4250		
	<b>50</b>			2810	3145	3375	3550	3775	3935	4075	4250		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.