



## SPECIFICATIONS

# TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



### 480/80 R 50 159 A8/B TL Traxion85

<b>EAN</b>							8714692327216							<b>Section Width</b>				500 mm	
<b>Nominal Tyre Pressure</b>							2,4 bar							<b>Overall Diameter</b>				2045 mm	
<b>Tyre Construction</b>							Radial							<b>Static Loaded Radius</b>				950 mm	
<b>Recommended Rim Width</b>							DW16L							<b>Rolling Circumference</b>				6225 mm	
<b>Permitted Rim Width</b>							DWL14L,							<b>SRI</b>				975	
							W/DW15L, W16L							<b>Tread Depth</b>				49 mm	
<b>Alternative Size Description</b>							18.4 R 50							<b>75% of the Tyre Volume</b>				550 l	
<b>Tyre Pressure (Bar)</b>																			
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80						

Load Capacity per tyre (kg)													
Speed (km/h)	10L	3080	3495	3925	4340	4770	5105	5400	5725	5965	6175	6425	6565
	10H	2375	2760	3135	3510	3770	4015	4210	4395	4550	4680		
	25	2465	2860	3255	3640	3910	4165	4370	4560	4720	4855		
	30	2375	2760	3135	3510	3770	4015	4210	4395	4550	4680		
	40			2930	3280	3525	3750	3935	4105	4250	4375		
	50			2930	3280	3525	3750	3935	4105	4250	4375		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.