



SPECIFICATIONS

TRAXION VERSA

The Vredestein Traxion Versa is a state-of-the-art agro-industrial tyre, ideal for telehandlers, backhoes, and compact wheel loaders operating on feedlots and for general around-the-farm maintenance. It is specifically designed for use on soft surfaces where optimal traction and flotation are required.

FEATURES:

Incorporating the unique Traxion design concept, the Versa ensures exceptional comfort and traction in the field.

A large cleat surface in the comfort zone provides extensive ground contact for optimal flotation.

The extended curved cleats enhance traction.

A reinforced sidewall and stabiliser ring provide robust damage protection.



500/70 R 24 IND 164 A8/B TL TRAXION VERSA

EAN		8714692309960	Section Width		515 mm				
Nominal Tyre Pressure		4,0 bar	Overall Diameter		1320 mm				
Tyre Construction		Radial	Static Loaded Radius		595 mm				
Recommended Rim Width		DW16L	Rolling Circumference		4020 mm				
Permitted Rim Width		DW15L, DW18L	SRI		625				
Alternative Size Description(s)		19.5 LR 24	Tread Depth (including tie bac)		39 mm				
EAN Tube		8714692332692	Tread Bar Height		3 mm				
			75% of the Tyre Volume		234 l				
Tyre Pressure (Bar)									
		1,60	2,00	2,40	2,80	3,20	3,60	4,00	4,40

Load Capacity per tyre (kg)									
Speed (km/h)	0	4460	5450	6445	7435	8425	9490	10410	11500
	10C	2910	3555	4200	4850	5495	6190	6790	7500
	25	2515	2970	3425	3885	4375	4795	5300	
	30	2465	2915	3360	3810	4290	4705	5200	
	40	2370	2800	3230	3665	4125	4525	5000	
	50	2370	2800	3230	3665	4125	4525	5000	

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.