



SPECIFICATIONS

TRACTION FLOTATION+

When you want a bumper crop, the last thing you want is compacted soil to spoil it. The excellent flotation properties of Vredestein Flotation+ ensures limited soil compaction to allow excellent seed germination.

FEATURES:

Wide tread design with a large ground contact surface area ensures excellent flotation properties and minimal soil compaction.

Unique tread design ensures excellent self-cleaning properties.

Excellent height/width ratio ensures optimal stability.



500/50 - 17 IMP 149 A8 TL FLOTATION+

EAN							8714692201042		Section Width				500 mm	
Nominal Tyre Pressure							2,8 bar		Overall Diameter				950 mm	
Tyre Construction							Bias		Static Loaded Radius				430 mm	
Recommended Rim Width							16.00		Rolling Circumference				2890 mm	
									Tread Depth				15 mm	
EAN Tube							8714692239083							
Tyre Pressure (Bar)														
		1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80	3,40		

LLV		Load Capacity per tyre (kg)										HLV
Speed (km/h)	10	2140	2410	2680	2940	3220	3480	3740	4020	4280	4540	5360
	25	1820	2050	2270	2500	2730	2960	3180	3420	3640	3860	4540
	30	1710	1930	2140	2360	2570	2780	3000	3220	3420	3640	4280
	40			1910	2100	2290	2490	2680	2870	3060	3240	3820
	50					2060	2240	2410	2580	2750	2920	3440

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.