



## SPECIFICATIONS

# FLOTATION

The Flotation Trac Implement Radial is characterised by its all-round capabilities, making it the perfect tyre for both arable and pasture land and for intensive transport activities. Its innovative tread profile and strong, flexible carcass construction have been designed to deliver top performance and prevent damage to the soil structure – whilst maintaining the ability to carry out transport activities at relatively high speeds.

## FEATURES:

Wide and flat tread contour with rounded shoulders preserves the soil structure and minimises rutting and crop damage.

Strong sidewall and robust bead construction ensures optimal durability and protection against punctures, cuts and abrasions.

Stable central tread section with open shoulder design ensures excellent operator comfort, optimal self-cleaning properties and enhanced traction characteristics.



## 520/50 R 17 IMP 147 D TL FLOTATION TRAC

<b>EAN</b>					8714692291593	<b>Section Width</b>				505 mm
<b>Nominal Tyre Pressure</b>					4,0 bar	<b>Overall Diameter</b>				965 mm
<b>Tyre Construction</b>					Radial	<b>Static Loaded Radius</b>				445 mm
<b>Recommended Rim Width</b>					16.00	<b>Rolling Circumference</b>				2970 mm
						<b>SRI</b>				450
						<b>Tread Depth</b>				17 mm
						<b>Tread Bar Height</b>				6 mm
						<b>75% of the Tyre Volume</b>				133 l
<b>Tyre Pressure (Bar)</b>										
		1,20	1,60	2,00	2,40	2,80	3,20	3,60	4,00	

<b>Load Capacity per tyre (kg)</b>									
Speed (km/h)	10	2435	2890	3310	3760	4195	4635	5095	5535
	25	2135	2535	2905	3300	3680	4070	4475	4860
	30	2045	2425	2775	3155	3520	3890	4275	4645
	40	1840	2180	2500	2840	3170	3500	3850	4180
	50	1635	1940	2225	2525	2820	3115	3425	3720
	65	1355	1605	1840	2090	2330	2575	2830	3075
	70	1230	1460	1675	1900	2120	2345	2575	2800

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.