



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



### 520/70 R 34 148 D TL Traxion+ (70 Series)

<b>EAN</b>						8714692276910		<b>Section Width</b>		540 mm	
<b>Nominal Tyre Pressure</b>						1,6 bar		<b>Overall Diameter</b>		1640 mm	
<b>Tyre Construction</b>						Radial		<b>Static Loaded Radius</b>		770 mm	
<b>Recommended Rim Width</b>						DW16L W/DW15L,		<b>Rolling Circumference</b>		4950 mm	
<b>Permitted Rim Width</b>						W16L, W/DW18L		<b>SRI</b>		775	
								<b>Tread Depth</b>		52 mm	
<b>EAN Tube</b>						8714692331411		<b>75% of the Tyre Volume</b>		360 l	
<b>Tyre Pressure (Bar)</b>											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

### Load Capacity per tyre (kg)

Speed (km/h)	10L	2570	2915	3275	3625	3980	4260	4505	4775
	10H	2130	2475	2810	3145	3380	3620		
	25	2195	2550	2900	3245	3485	3735		
	30	2130	2475	2810	3145	3380	3620		
	40		2355	2680	2995	3220	3450		
	50		2260	2570	2875	3085	3310		
	65			2445	2735	2940	3150		
	70			2225	2490	2675	2865		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT [WWW.VREDESTEINTYRES.COM.AU](http://WWW.VREDESTEINTYRES.COM.AU)