



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



520/70 R 38 150 D TL Traxion+ (70 Series)

EAN						8714692276958		Section Width			540 mm	
Nominal Tyre Pressure						1,6 bar		Overall Diameter			1750 mm	
Tyre Construction						Radial		Static Loaded Radius			815 mm	
Recommended Rim Width						DW16L W/DW15L,		Rolling Circumference			5275 mm	
Permitted Rim Width						W16L, W/DW18L		SRI			825	
								Tread Depth			52 mm	
EAN Tube						8714692331466		75% of the Tyre Volume			405 l	
Tyre Pressure (Bar)												
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00			

Load Capacity per tyre (kg)

Speed (km/h)	10L	2750	3120	3500	3875	4255	4560	4820	5110
	10H	2280	2645	3010	3365	3615	3850		
	25	2350	2725	3100	3470	3725	3970		
	30	2280	2645	3010	3365	3615	3850		
	40		2520	2865	3205	3445	3670		
	50		2415	2745	3075	3300	3520		
	65			2615	2930	3145	3350		
	70			2380	2665	2860	3050		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT WWW.VREDESTEINTYRES.COM.AU