



## SPECIFICATIONS

# TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



### 520/85 R 42 157 A8/B TL Traxion85

EAN					8714692244544		Section Width			555 mm	
Nominal Tyre Pressure					1,6 bar		Overall Diameter			1930 mm	
Tyre Construction					Radial		Static Loaded Radius			905 mm	
Recommended Rim Width					DW18L		Rolling Circumference			5785 mm	
Permitted Rim Width					DW16L, DD18L		SRI			925	
Alternative Size Description					20.8 R 42		Tread Depth			T52 mm	
							75% of the Tyre Volume			510 l	
Tyre Pressure (Bar)											
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00		

### Load Capacity per tyre (kg)

Speed (km/h)	10L	3355	3810	4275	4730	5195	5565	5885	6240
	10H	2590	3005	3415	3825	4105	4415		
	25	2685	3120	3545	3965	4260	4580		
	30	2590	3005	3415	3825	4105	4415		
	40		2810	3195	3575	3840	4125		
	50		2810	3195	3575	3840	4125		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.