



SPECIFICATIONS

TRAXION 85

Engineered in the Netherlands, the Vredestein Traxion85 is a premium combination of superb traction, optimal ride comfort and durability. Manufactured with state-of-the-art technology, the Traxion85 makes the roughest Australian paddocks feel like a turf farm.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Rounded shoulders prevents damage to the turf and sensitive crop areas.

Reinforced bead with extra strengthening layers ensures optimum stability at high speeds and on sloping terrains.

Advanced tread design ensures excellent traction and unbeatable ride comfort.



520/85 R 46 158 A8/B TL Traxion85

EAN					8714692244544	Section Width				535 mm
Nominal Tyre Pressure					1,6 bar	Overall Diameter				2050 mm
Tyre Construction					Radial	Static Loaded Radius				930 mm
Recommended Rim Width					DW16L	Rolling Circumference				6150 mm
Permitted Rim Width					DW18L	SRI				975
Alternative Size Description					20.8 R 46	Tread Depth				51 mm
						75% of the Tyre Volume				650 l
Tyre Pressure (Bar)										
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	

Load Capacity per tyre (kg)

Speed (km/h)	10L	3505	3975	4465	4940	5425	5810	6145	6515
	10H	2705	3140	3570	3995	4290	4550		
	25	2805	3255	3705	4145	4450	4720		
	30	2705	3140	3570	3995	4290	4550		
	40		2935	3335	3735	4010	4250		
	50		2935	3335	3735	4010	4250		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.