



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



540/65 R 24 140 D TL Traxion+ (65 Series)

EAN	8714692259777	Section Width	540 mm
Nominal Tyre Pressure	1,6 bar	Overall Diameter	1315 mm
Tyre Construction	Radial	Static Loaded Radius	620 mm
Recommended Rim Width	DW16L	Rolling Circumference	3960 mm
Permitted Rim Width	W/DW15L, W16L, W/DW18L	SRI	625
		Tread Depth	47 mm
		75% of the Tyre Volume	260 l

Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	10L	2070	2350	2635	2915	3200	3425	3615	3835
	10H	1715	1990	2265	2495	2695	2875		
	25	1770	2050	2330	2575	2775	2965		
	30	1715	1990	2265	2495	2695	2875		
	40		1895	2155	2375	2565	2740		
	50		1820	2065	2280	2460	2625		
	65			1970	2170	2345	2500		
	70			1790	1975	2130	2275		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.