



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



540/65 R 28 142 D TL Traxion+ (65 Series)									
EAN		8714692259807				Section Width		540 mm	
Nominal Tyre Pressure		1,6 bar				Overall Diameter		1410 mm	
Tyre Construction		Radial				Static Loaded Radius		660 mm	
Recommended Rim Width		DW16L				Rolling Circumference		4240 mm	
Permitted Rim Width		W/DW15L#,				SRI		675	
		W16L, W/DW18L				Tread Depth		47 mm	
EAN Tube		8714692239809				75% of the Tyre Volume		285 l	
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	<b>10L</b>	2215	2510	2820	3120	3425	3665	3865	4105
	<b>10H</b>	1835	2130	2420	2670	2880	3045		
	<b>25</b>	1890	2195	2495	2750	2970	3140		
	<b>30</b>	1835	2130	2420	2670	2880	3045		
	<b>40</b>		2030	2305	2540	2745	2900		
	<b>50</b>		1945	2210	2440	2630	2785		
	<b>65</b>			2105	2320	2505	2650		
	<b>70</b>			1915	2115	2280	2410		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.