



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



### 540/65 R 30 150 D TL Traxion+ (65 Series)

<b>EAN</b>							8714692076671		<b>Section Width</b>				540 mm	
<b>Nominal Tyre Pressure</b>							2,4 bar		<b>Overall Diameter</b>				1460 mm	
<b>Tyre Construction</b>							Radial		<b>Static Loaded Radius</b>				670 mm	
<b>Recommended Rim Width</b>							DW16L		<b>Rolling Circumference</b>				4400 mm	
<b>Permitted Rim Width</b>							W/DW15L# ,W16L,		<b>SRI</b>				700	
							W/DW18L		<b>Tread Depth</b>				47 mm	
<b>EAN Tube</b>							8714692331381		<b>75% of the Tyre Volume</b>				305 l	
<b>Tyre Pressure (Bar)</b>														
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80	

<b>Load Capacity per tyre (kg)</b>													
Speed (km/h)	<b>10L</b>	2285	2590	2905	3215	3530	3780	3990	4235	4415	4620	4825	5025
	<b>10H</b>	1895	2195	2495	2755	2975	3135	3355	3525	3670	3850		
	<b>25</b>	1950	2265	2575	2840	3065	3230	3460	3630	3785	3970		
	<b>30</b>	1895	2195	2495	2755	2975	3135	3355	3525	3670	3850		
	<b>40</b>		2090	2380	2620	2830	2985	3195	3355	3495	3670		
	<b>50</b>		2005	2280	2515	2715	2860	3065	3215	3355	3520		
	<b>65</b>			2170	2395	2585	2725	2920	3065	3195	3350		
	<b>70</b>			1975	2180	2350	2480	2655	2790	2905	3050		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.